

SW10 FULL ENERGY & SW19 LOW ENERGY | SINGLE & DOUBLE



Installation is Simplified

The operator defaults are set at the factory. With self-learning and self-tuning, the operator can be installed and operational in minutes. In addition, the unique slim-line design offers non-handed (right or left handed opening) operation, full mechanical stops and numerous interface options for sensors, push plates, fire alarms and electric locks. The on-board diagnostics simplify troubleshooting when needed. Both the SW10 (Full Energy Swing Door) and the SW19 (Low Energy Swing Door) can be configured for a surface mount (push or pull)

**Built-In Safety and Functionality** 

The industry's quietest operator can be customized with silver, bronze, gold, marble or wood 'skins' to blend seamlessly with surroundings. Safety is assured with meeting all ADA requirements and ANSI standards. In addition, the Tucker Advanced Programmer (TAP) is an option for accessing additional programming features.

### TOUCHLESS & PUSH PLATES DOOR OPENING SYSTEM

MICROWAVE TOUCHLESS SENSORS, CARD READERS OR PUSH PLATES







# MOTION & PRESENCE SENSORS DOOR OPENING SYSTEM TAP CONTROLLERS

OUR SENSORS HAVE BEEN DESIGNED TO BE COMPLIANT WITH ANSI 156.10 AND COMPATIBLE



PIISH



THE BAT

FUNCTIONS KEYBOARD/PROGRAMMING DISPLAY





# **FEATURES & BENEFITS**

- NON-HANDED
- SELF-TUNING, SELF-LEARNING
- EXTREMELY SILENT
- COMPLIES WITH ANSI A156.19 & A156.10
- UL CERTIFIED FOR USE AS FIRE DOOR OPERATORS (3 HOUR RATING)
- COMPLIES WITH ALL US AND CANADIAN ADA REQUIREMENTS
- REVERSE ON OBSTRUCTION
- CHOICE OF SPRING OR POWER CLOSE



## EE changes skin on demand.













SINGLE WIDTH (SINGLE-W) = 39"/45"/47"/51" - 990 mm / 1143 mm/ 1194 mm/ 1295 mm DOUBLE WIDTH (DOUBLE-W) = 75" / 87" / 91" / 99" - 1905 mm / 2210 mm / 2311 mm / 2514 mm



POWDER COATED STEEL END CAPS